

DC DIGITAL HIGH VOLTAGE TESTER **SEW**



- DC 30kV measurement with direct reading
- 4000-count LCD
- Input impedance : 200 Mohm
- Auto-ranging : DC 4.000kV / 30.00kV
- Must be used with an approved hot stick, such as HS-175, HS-120, HS-120R.
- Backlight function
- Auto power off
- Power source : 1.5V(AA) alkaline battery × 2
- Low battery indication(Multi-level)
- Meets EN IEC 61326-1
- Protection class : IP66



• TER-213 60mm



• TER-213



• TER-45M/M A



SPECIFICATIONS

DC Voltage

Range	Resolution	Accuracy
4.000 kV	0.001 kV	$\pm(2.0\%rdg + 0.08kV)$
30.00 kV	0.01 kV	

General

Low battery indication	√ (Multi-level)
Operating temperature & humidity	0°C~40°C, 80% Max.
Storage temperature & humidity	-10°C~50°C, 80% Max.
Dimensions	Master stick : 490(L) × 101(W) × 118(D)mm Cable length : 5 meters approx.
Weight (battery included)	Approx. g
Power source	1.5V (AA) Alkaline battery × 2
Accessories	Instruction manual "Y" contact electrode Test hook(contact electrode) Insulated rod (HS-500) Alkaline batteries Carry case Piercing tip

INSTRUMENT LAYOUT

- ① LCD
- ② ON/OFF Button
- ③ 5-meter earthing cable
- ④ Backlight Button
- ⑤ Master Stick
- ⑥ Big alligator clip for earthing
- ⑦ Adapter End
- ⑧ Battery Cover

