

ANALOGUE INSULATION TESTER



- High quality Taut Band movement.
- Battery operated.
- Solid state circuitry.
- Battery check feature.
- External voltage : warning indication.
- Automatic circuit discharge.
- Three insulation test voltages(DC) :
250V, 500V, 1000V
- Continuity test : 50 Ω
- AC voltage measurement : 600V
- Color-coded scale.
- Fuse protected.

SPECIFICATIONS

Insulation Resistance

Test voltage (DC V)	250V / 500V / 1000V
Measuring ranges	0-100M Ω / 0-200M Ω / 0-400M Ω
Output voltage on open circuit	Rated test voltage +10%
Accuracy	$\pm 5\%$ of indicated value
Short circuit current	2mA DC
Power consumption	190mA

Continuity

Measuring range	0 -50 Ω & ∞
Accuracy	$\pm 5\%$ of scale length
Open circuit voltage	4V DC Approx.
Short circuit current	145mA DC Approx.
Power consumption	200mA

AC Voltage

Range	0-600V AC
Accuracy	$\pm 2.5\%$ of full scale
Line frequency range	40 -1k Hz

General

Dimensions (with housing front cover)	175(L) $\times$ 85(W) $\times$ 75(D)mm
Weight (battery included)	Approx. 600g
Power source	1.5V (AA) $\times$ 8
Safety standard	EN 61010-1 CAT III 600V EN 61326-1
Accessories	Instruction manual Test leads Shoulder belt Batteries