# ANALOGUE INSULATION TESTER SEW



## **FEATURES**

- High quality taut band movement.
- Three insulation test voltages(DC): 250V, 500V, 1000V.
- Two continuity test on "low ohms" :  $3\Omega$  &  $500\Omega$ .
- AC voltmeter with linear scale up to 600 Vac.
- 200mA short circuit current for continuity.
- 1mA test current on insulation test at nominal voltage.
- Automatic discharge of capacitive and inductive circuit with charge stored in the circuit under test.
- Live warning and display of external voltage presence.
- Fuse, air gap, crowbar and overload protected.
- On line battery monitoring shows if battery is
- Manual zero ohm adjustment.
- Low battery consumption.
- Mirror scale.
- Push and turn locking switch for continuous and hand free testing.
- Supplied with high quality test leads.
- BS 16<sup>th</sup> edition.

### **SPECIFICATIONS**

### **Insulation Resistance**

Test voltage (DC V)	250V	500V	1000V	
Output voltage on open circuit	Rated test voltage +10%			
Measuring ranges	0-100ΜΩ	0-200ΜΩ	0-400ΜΩ	
Mid-scale value	1ΜΩ	2ΜΩ	4ΜΩ	
Scale multiplier	×1/2	×1	×2	
Accuracy	± 5% of indicated value			
Output short-circuit current	Approx. 1.3mA			

Continuity

Measuring ranges	3Ω / 500Ω
Zero $\Omega$ adjustment by knob	$\checkmark$
Output short-circuit current	≥ 200 mA
Accuracy	± 1.5% of scale length

**AC Voltage** 

Range	0-600V AC
Accuracy	± 3% of scale length

#### General

Voltage warning	Warning light circuit live lit from 90Vdc / 70Vac, Buzzer beep from 24Vac/dc
Dimensions	207(L) × 188(W) × 68(D)mm
Weight (battery included)	Approx. 870g
Power source	1.5V (AA) × 6
Safety standard	IEC/EN 61010-1 CAT III 600V IEC/EN 61010-2-034 IEC/EN 61326-1
Accessories	Instruction manual Test leads Shoulder belt Batteries

STANDARD ELECTRIC WORKS CO., LTD. www.sew.com.tw