

## Analogue Multimeter



CE

**ST-365 TR**

DC volts	0-0.1 / 0.5 / 2.5 / 10 / 50 / 250 / 1000V (20kΩ/V)
AC volts	0-10 / 50 / 250 / 1000V
DC mA	50uA / 2.5 / 25 / 250mA
OHMS	2k / 20k / 200k / 2M / 20MΩ (20 Mid-Scale)
Accuracy	±3% F.S. DC. ± 4% F.S. AC.
Sensitivity	20kΩ/V DC. 8kΩ/V AC
dB	-10dB ~ +22dB
hFE	0-1000
ICEO	150uA, 1.5mA, 15mA, 150mA
LV	3V
Dimensions	100(L) × 150(W) × 41(D)mm
Weight (battery included)	Approx. 300g
Power source	1.5V(AA) battery × 2 9V(6F22) battery × 1
Safety standard	EN 61010-1 CAT II 1000V



CE

**ST-367 TR**

DC volts	0-0.1 / 0.5 / 2.5 / 10 / 50 / 250 / 1000V (20kΩ/V)
AC volts	0-10 / 50 / 250 / 1000V
DC mA	50uA / 2.5 / 25 / 250mA
OHMS	2k / 20k / 200k / 2M / 20MΩ (20 Mid-Scale)
Accuracy	±3% F.S. DC. ± 4% F.S. AC.
Sensitivity	20kΩ/V DC. 8kΩ/V AC
dB	-10dB ~ +22dB
hFE	0-1000
ICEO	150uA, 1.5mA, 15mA, 150mA
LV	3V
Dimensions	100(L) × 150(W) × 41(D)mm
Weight (battery included)	Approx. 300g
Power source	1.5V(AA) battery × 2 9V(6F22) battery × 1
Safety standard	EN 61010-1 CAT II 1000V EN 61010-2-030 EN 61326-1



CE

**ST-368 TR**

DC volts	0-0.1 / 0.5 / 2.5 / 10 / 50 / 250 / 1000V (20kΩ/V)
AC volts	0-10 / 50 / 250 / 1000V
DC mA	50uA / 2.5 / 25 / 250mA
OHMS	2k / 20k / 200k / 2M / 20MΩ (20 Mid-Scale)
Accuracy	±3% F.S. DC. ± 4% F.S. AC.
Sensitivity	20kΩ/V DC. 9kΩ/V AC
dB	-10dB ~ +22dB
hFE	0-1000
LED check	√
Battery check	GOOD or BAD
ICEO	150uA, 1.5mA, 15mA, 150mA
LV	3V~0V
Dimensions	100(L) × 150(W) × 41(D)mm
Weight (battery included)	Approx. 340g
Power source	1.5V(AA) battery × 2 9V(6F22) battery × 1
Safety standard	EN 61010-1 CAT II 1000V EN 61010-2-030 EN 61326-1