

Analogue Multimeter



FEATURES

- High quality Taut Band movement
- Easy to read 3-color scale for mistake-proof reading
- Mirror scale makes reading pointer easy
- Safety features on all ranges
- Fuse protection
- Safety OFF position
- dB measurement
- Built-in stand makes reading and measuring easy

SPECIFICATIONS

DC Voltage

Ranges	0.25 / 1 / 2.5 / 10 / 50 / 250 / 1000V
Accuracy	±2% of full scale
Sensitivity	50kΩ / V

AC Voltage

Ranges	2.5 / 10 / 50 / 250 / 1000V
Accuracy	±3% of full scale
Sensitivity	10kΩ / V
Decibelmeter	-20 to 62dB 0dB=1mW / 600Ω direct scale: -20 to +10dB

DC Current

Ranges	25uA / 1mA / 25mA / 500mA, 10A (on separate input)
Accuracy	±2% of full scale
Sensitivity	250mV

AC Current

Range	10A
Accuracy	±3% of full scale

Resistance

Ranges	R × 1	0.2 to 20kΩ
	R × 10	2 to 200kΩ
	R × 100	20 to 2MΩ
	R × 1000	200 to 20MΩ
Accuracy	±3% of full scale	

General

Dimensions	160(L) × 100(W) × 45(D)mm
Weight (battery included)	Approx. 380g
Power source	1.5V(AA) battery × 2
Safety standard	EN 61010-1 CAT III 600V EN 61326-1 EN 61010-2-030
Accessories	Instruction manual Test leads Batteries