

Bench Type



- **Dimension** : 91(L) × 103(W) × 100(D)mm
- **Deflection Angle** : 90°
- **Scale Length** : Approx. 65mm
- **Terminal**:
4mm socket captive head, suitable for wire or pin-type test lead.
- **Material and Color** :
Acrylic resin meter cover, white scale plate, plastic stand in black.
- **Safety Standard** :
IEC/EN 61010-1 CAT II 300V
EN 61326-1 EN 61000-4-2 EN 61000-4-3



ED-205

Name	Range	No.	
AC Ammeter (Rectifier Type) Accuracy: ±2.5% F.S.	1 Range	1A 205ACA 100	
		500mA 205ACA 101	
		5A 205ACA 102	
	2 Ranges	1/10A 205ACA 200	
		10/100mA 205ACA 201	
		100/500mA 205ACA 202	
		500mA/1A 205ACA 203	
		80/200mA 205ACA 204	
	3 Ranges	50mA/500mA/5A 205ACA 301	
		500mA/1A/5A 205ACA 302	
		1/2.5/5A 205ACA 303	
		30/100/500mA 205ACA 305	
AC Voltmeter (Rectifier Type) Accuracy: ±2.5% F.S.	1 Range	5V 205ACV 100	
		10V 205ACV 101	
		20V 205ACV 102	
		50V 205ACV 103	
	2 Ranges	250V 205ACV 104	
		10/100V 205ACV 201	
		3/30V 205ACV 202	
	3 Ranges	5/15V 205ACV 203	
		15/30/50V 205ACV 301	
		30/50/100V 205ACV 302	
DC Ammeter (Moving Coil Type) Accuracy: ±2.0% F.S.	1 Range	50µA 205DCA 100	
		100µA 205DCA 101	
		500µA 205DCA 102	
		3mA 205DCA 103	
		10mA 205DCA 104	
		100mA 205DCA 105	
		200mA 205DCA 106	
		300mA 205DCA 107	
		500mA 205DCA 108	
		500µA 205DCA 109	
		1A 205DCA 110	
		2.5A 205DCA 111	
		3A 205DCA 112	
		5A 205DCA 113	
		10A 205DCA 114	
		1mA 205DCA 115	
		1/10mA 205DCA 200	
		1/5A 205DCA 201	
		2 Ranges	1/10A 205DCA 202
			50/500mA 205DCA 203
			50/500µA 205DCA 204
		3 Ranges	50mA/500mA/5A 205DCA 301
			100mA/1A/5A 205DCA 302
			1/5/10A 205DCA 303
50/500/5000µA 205DCA 304			
100µA/500µA/1mA 205DCA 305			

Name	Range	No.
DC Voltmeter (Moving Coil Type) Accuracy: Class 2.0	1 Range	1V 205DCV 101
		3V 205DCV 102
		5V 205DCV 103
		6V 205DCV 104
		10V 205DCV 105
		15V 205DCV 106
	2 Ranges	20V 205DCV 107
		50/500mV 205DCV 200
		1/10V 205DCV 202
		1/5V 205DCV 203
		2/20V 205DCV 204
		3/15V 205DCV 205
		5/10V 205DCV 206
		5/15V 205DCV 207
		10/50V 205DCV 208
		30/60V 205DCV 209
3 Ranges	3/10/15V 205DCV 303	
	3/15/300V 205DCV 304	
	3/15/30V 205DCV 305	
	3/30/300V 205DCV 306	
	30/100/300V 205DCV 307	
	DC (Galvanometer Type) Accuracy: Class 2.0	± 0.1mA 205G 100
		± 0.5mA 205G 101
± 10V 205G 102		
± 1A 205G 103		
± 3.5G 205G 104		
± 3.5mA 205G 105		
± 30G 205G 106		
± 30mA 205G 107		
± 35G 205G 109		
± 35mA 205G 110		
± 50G 205G 111		
± 60uA 205G 112		
Custom Accuracy: Class 2.0	1A-0-5A 205DC 101	
	20µA-0-100µA 205DC 102	
	20mA-0-100mA 205DC 103	
	5V-0-15V 205DC 104	
	50mA/500mA/5A 205DC 105	
3/15/300V 205DC 106		

Special specification: Pls contact with SEW.