

Test Leads

AL-56FL



CE

- AL-56FL is an ideal tool which shows the indication of live voltage even with blown fuse
- 2 replaceable fast-acting fuses (1000V, 11A with internal rating of 30kAAC/DC)
- Fuses provide additional testing protection
- Helps to prevent a possible mis-indication when there is voltage present
- CAT III 1000V, CAT IV 600V, 11A with protective cover
- 2mm probe tips, removable 4mm brass caged banana probe tips are also included
- Includes high-quality silicone test leads, 1.5m
- Wipe the fused test probes and silicone test leads periodically with a damp cloth and detergent. Do not use abrasives or solvents
- Operating temperature: -20°C~50°C (-5°F to 120°F)
- One year warranty
- Can't be used in amperage mode with blown fuse
- Rating:
EN 61010-031 CAT III 1kV 11A / CAT IV 600V 11A

AL-57FL



CE

- AL-57FL is an ideal tool which shows the indication of live voltage even with blown fuse
- 2 replaceable fast-acting fuses (1000V, 11A with internal rating of 30kAAC/DC)
- Fuses provide additional testing protection
- Helps to prevent a possible mis-indication when there is voltage present
- CAT III 1000V, CAT IV 600V, 11A with protective cover
- 2mm probe tips, removable 4mm brass caged banana probe tips are also included
- Includes high-quality silicone test leads, 1.5m
- Wipe the fused test probes and silicone test leads periodically with a damp cloth and detergent. Do not use abrasives or solvents
- Operating temperature: -20°C~50°C (-5°F to 120°F)
- One year warranty
- Can't be used in amperage mode with blown fuse
- Rating:
EN 61010-031 CAT III 1kV 11A / CAT IV 600V 11A

AL-58, AL-58 HV



CE

- Large test probe handle with shrouded 4mm brass caged banana plug tip
- Super insulated silicone wire, 2.5m
- Material: silicon
- Outside diameter: **AL-58: 6.5mm / AL-58 HV: 7mm**
- Safety straight input plug connect with extra green guard
- Rating:
EN 61010-031
CAT III 15kVdc 5mA
- ⚠ Warning:
Only available for insulation tester